

FMHC220-FC-MDB03



Modbus-RTU

Flush mount, 230VAC thermostat, for Fan Coil B.M.S. applications, with Modbus protocol

General

The FMHC220-FC-MDB03 is a highly versatile, stand alone thermostat, suitable for Building Management System application, with Modbus communication protocol.

With multiple, selectable modes of operation, the FMHC220-FC-MDB03 offers suitability to 2-Pipe, 4-Pipe or no valve Fan Coil system, electrical heating element option, and can function as either Coo/Heat or Cool Only thermostat.

Using DIP switch, technician can select between applying Auto-Change-Over sensor, or alternatively utilizing a contact input for Economy mode to save energy. In addition, it offers the Auto-Fan feature to work at either Cool, or Heat or at both. Additional features, such as Set Point Temp. Limits, Dead Zone and Room Temperature Offset are all implemented and changeable.

Overall, the FMHC220-FC-MDB03 offers numerous options, nonetheless setting is simple and user friendly.


Features

- Flush mount, 230VAC thermostat
- · 2 separate outputs for Cool & Heat
- DIP switch selectable options:
 - * Auto-Change-Over sensor or Contact input
 - * 2-pipe or 4-pipe system
 - * 1 or 3 fan speed control + Auto Speed
 - * With or without Auto-Change-Over mode
 - * Set point & room temp. display on LCD , or set point temp. display only
 - * Always Auto-fan or Auto-fan selectable
 - * Internal or external temperature sensor
- Modes: Cool/ Heat / Auto- Change-Over/ Fan Only
- Contact input changes to Economy mode or turns unit off (Optional)
- Cool Only thermostat option
- Electrical heater option
- Disable Fan operation option (only in Cool, only in Heat, or in both)
- Set point limits 10...30°C
- 3 Auto-Fan types:
 - * Auto-fan in Cool & Heat
 - * Auto-fan only in Cool
 - * Auto-fan only in Heat
- · Password for protected setting
- Pushbutton beeper option
- Hand held remote control (RT03) option


File: FMHC220-FC-MDB03 Rev.1 Date: 01.06.2010



FMHC220-FC-MDB03



Specifications Temperature Range 10° - 30°C Accuracy ±1°C Weight 0.200 Kg Plastic PC/ABS Scale °C UL94V-0 Flammability Color White/Black/Silver/other Temperature Input Thermistor 50K@25°C



Accessories	
Part Number	Description
TS01	External Temperature Sensor - 80 cm Cable
TS02	External Temperature Sensor - 300 cm Cable
RS01	Room temperature sensor
RT03	Hand held remote control